

# Pressure Gauges

## Dry & Liquid Filled Utility Gauges - 2-1/2" Diameter Face

Dry Part #	Liquid Filled Part #	Pressure Range
D-30HG-25	G-30HG-25	Vac 30 Hg
D-30HG/15-25	G-30HG/15-25	Vac 30 Hg / 15 psi
D-30HG/30-25	G-30HG/30-25	Vac 30 Hg / 30 psi
D-30HG/60-25	G-30HG/60-25	Vac 30 Hg / 60 psi
D-30HG/100-25	G-30HG/100-25	Vac 30 Hg / 100 psi
D-30HG/160-25	G-30HG/160-25	Vac 30 Hg / 160 psi
D-30HG/200-25	G-30HG/200-25	Vac 30 Hg / 200 psi
D-30HG/300-25	G-30HG/300-25	Vac 30 Hg / 300 psi
D-15-25	G-15-25	15 psi
D-30-25	G-30-25	30 psi
D-60-25	G-60-25	60 psi
D-100-25	G-100-25	100 psi
D-160-25	G-160-25	160 psi
D-200-25	G-200-25	200 psi
D-300-25	G-300-25	300 psi
D-400-25	G-400-25	400 psi
D-600-25	G-600-25	600 psi
D-800-25	G-800-25	800 psi
D-1M-25	G-1M-25	1000 psi
D-1500-25	G-1500-25	1500 psi
D-2M-25	G-2M-25	2000 psi
D-3M-25	G-3M-25	3000 psi
D-5M-25	G-5M-25	5000 psi
D-6M-25	G-6M-25	6000 psi
D-10M-25	G-10M-25	10,000 psi
	G-15M-25	15,000 psi



### Options

For alternate face sizes:  
(Change end number)  
15 = 1-1/2" Face  
2 = 2" Face

For Rear Center Connection add "RC"  
at the end of the part number

*Example* : G-300-2-RC  
Glycerin filled, 0-300 psi, 2" Face  
1/4" NPT Rear Center Connection

For "C" Clamp Panel Mounting add "C"  
or Flange Panel Mounting add "FP".

## Pressure Diagnostic Kit

Whether you are a Service Technician in the field, a mechanic in the shop, or you maintain your own equipment, you need to be able to monitor hydraulic system pressure. With our new Pressure Diagnostic Kits, you can check pressures quickly, easily and accurately. We offer two separate kits containing gauges, test hoses and test point couplers. Our original kit (PDK) contains M16x2.0 Screw-type test point couplers, while our latest kit contains quick disconnect style test couplers. Standard gauge pressures are 1000, 3000 & 6000 psi. If alternate pressure gauges are desired, please specify before ordering.

**PDK** M16 x 2.0 Screw-type Test Couplers  
**PDK2** Quick Disconnect Couplers

